



# Proof, Photo & Production media

## PRODUCT DATASHEET



### EFI Gravure Proof Paper 4245XF Semimatt



#### Description:

The EFI Gravure Proof Paper 4245XF Semimatt is a universal, PE-coated, microporous proof paper for offset and gravure printing. The PEFC certified paper is excellent for dye and pigment based inks. The substrate is certified by FOGRA and is supplied with an EFI-FOGRA-PEFC back print. Due to the very large color gamut the printing substrates PS2, PS3 and PS4 are covered by ISO 12647-2. The very similar white point of the EFI Gravure Proof Paper 4245XF Semimatt to ISO 12647-7 resp. Fogra39 enables proofing without paper white simulation.



#### Application:

Proofing  
Photo



#### Technical data:

Weight	245 g/m <sup>2</sup>
Caliper	260 μm
Opacity	96 %
Gloss	54% [75°]
CIE L*a*b*	94,7   0,0   -1,5
Storage	15-30°C (40-60% RH)

#### Size

Sheets	Rolls	Core	Rolls	Core
DIN A4 (210 x 297 mm)	25,4 cm x 30 m (10")	3" *)	91,4 cm x 30 m (36")	3" *)
SUPER A4 (241 x 340 mm)	32,9 cm x 30 m (13")	3" *)	106,7 cm x 30 m (42")	3" *)
DIN A3 (297 x 420 mm)	36,0 cm x 30 m (14,17")	3" *)	111,8 cm x 30 m (44")	3" *)
DIN A3+ (330 x 483 mm)	43,2 cm x 30 m (17")	3" *)	135,0 cm x 30 m (53,125")	3" *)
A3++ (329 x 558 mm)	45,7 cm x 30 m (18")	3" *)	137,0 cm x 30 m (54")	3" *)
DIN A2 (420 x 594 mm)	50,8 cm x 30 m (20")	3" *)	152,4 cm x 30 m (60")	3" *)
DIN A1 (594 x 841 mm)	61,0 cm x 30 m (24")	3" *)		

\*) supplied with each two adapters 3" to 2" core



Important: Before using our print media, please verify that it is suitable for use with your printer. We shall not assume liability for non-performance of the print media resulting from changes beyond our control in printing inks or printers. Specifications are subject to change without notice. This product data sheet is intended to be used as a guideline only. Storing conditions: Please keep product in the supplied boxes for best possible protection. Product must be stored in a cool and dry environment, exposure to sun light is to be avoided.